

PRODUCT INFO

BACK-ROLLER CORE

Rear pannier with roll closure and QL2.1 system

QL2.1
system

IP 64

PD620

PS490

PFAS
free



- D-ring for shoulder strap (optional)
- Buckles for closing the rolling closure
- Lateral 3M Scotchlite reflector on both sides

Carrying handle for mounting
and releasing the QL2.1 system

QL2.1 bar and hooks for quick
fastening and release



Semi-elliptical hook rail with QL hook
(adjustable in 15° steps)

Edge protector with slots for mounting the
Pannier Carrying System

Height cm/in	Width cm/in	Depth cm/in	Volume L/cu.in.	Weight g/oz.	Max. capacity kg/lbs.
42/16.5	23/32 9/12.6	17/6.7	20/1220	820/28.9	9/19.8

SPECIFICATIONS:

- + Waterproof bike pannier ideal as starter model
- + QL2.1 mounting system for racks up to 16 mm
- + Bag made of PVC coated polyester fabric
- + 18 mm & 20 mm hook available as separate accessory (e. g. for e-bikes)
- + Prepared for Stabilizing Insert
- + Including reduction pieces for tube diameters 8, 10 and 12 mm; with anti-scratch function reducing abrasions on rack
- + Top QL hooks and lower sliding hook adjustable without requiring any tools
- + Lower hook rail made of two-component „hard-soft“ synthetic reduces abrasions on carrier
- + Can be used individually (e.g. for shopping, sports, picknick)
- + Highly reflective Scotchlite reflector
- + Easy to clean inside

Contents: Pannier with reduction inserts for 8, 10 and 12 mm

Optional accessories: Pannier Stabilizing Insert, Packing Cubes/Commuter Insert for Panniers, Pannier Carrying System, Shoulder strap (No. E172), QL2 Lock / QL2 Lock keyed alike (F3913/F3915)

Attention: Maximum load per pannier is 9kg / 20 lbs. We recommend weighing each loaded pannier to confirm that the maximum allowance of the pannier fixation is not exceeded. This practice is advised for both rear and front panniers. **CAUTION:** The maximum weight capacity of every carrier model is different. Please observe the maximum weight allowance of the carrier fitted to your bicycle. **Note:** Sometimes the maximum capacity of the panniers fixing system can exceed the maximum capacity of the carrier. **DO NOT** exceed the maximum capacity of the carrier! **Note,** that the use of panniers will significantly influence the handling properties of your bicycle.

Attention: As abrasion cannot be ruled out, we recommend that all points where the mounting system contacts the bicycle rack or frame be protected by scratch protection film.

Note: In order to meet standard IP64 (6=dustproof 4=protected against splash water coming from all directions) the lid must be rolled 3-4 times.

